

WHAT IS CLAIMED IS:

1. A bow sight, comprising:

at least one bow sight housing, said bow sight housing

5 having at least one sight pin; and

at least one light collecting mechanism carried by
said bow sight housing, wherein said at least one light
collecting mechanism defines at least one coil shape.

Sub
A1

10 2. The bow sight of Claim 1, wherein said at least one
light collecting mechanism defines a plurality of coil
shapes.

3. The bow sight of Claim 1, wherein said at least one
15 bow sight housing encases said at least one light
collecting mechanism.

Sub
A2

4. The bow sight of Claim 1, wherein said at least one
light collecting mechanism is at least one fiber optic
20 filament.

5. The bow sight of Claim 4, wherein said at least one
fiber optic filament is carried in a coil fashion by said
at least one bow sight housing.

Sub
A3

6. The bow sight of Claim 4 further comprising a support, wherein said at least one fiber optic filament is wrapped multiple times around said support, said at least one fiber optic filament is at least partially carried by said at least one sight pin, and said support is substantially encased within said at least one bow sight housing.

7. The bow sight of Claim 1, wherein said at least one bow sight housing further comprises at least one removable encasement.

8. The bow sight of Claim 7, wherein said at least one light collecting mechanism is at least one fiber optic filament.

9. The bow sight of Claim 8, wherein said at least one fiber optic filament is coiled within said at least one encasement.

10. The bow sight of Claim 8 further comprising a support, wherein said at least one fiber optic filament is coiled around said support, and wherein said support is housed within said at least one encasement.

11. The bow sight of Claim 1, wherein said ~~at least~~
~~one~~ bow sight housing is rotatable.

*Sub
A45*

12. A light collecting bow sight assembly, comprising:
at least one bow sight, said at least one bow sight
being rotatable and having at least one sight pin;
at least one light collector; and
at least one encasement for housing, said at least one
light collector.

10040151-010200

13. The light collecting bow sight assembly of Claim
12, wherein said at least one light collector is at least
one optical filament.

*Sub
A45*

14. The light collecting bow sight assembly of Claim
13, wherein said ~~at least one~~ optical filament is coiled
within said at least one bow sight and is at least
partially carried by said ~~at least one~~ sight pin.

20 15. The light collecting bow sight assembly of Claim
13, wherein said at least one fiber optic filament is
coiled a plurality of revolutions within said ~~at least one~~
encasement.

16. The light collecting bow sight assembly of Claim 15 further comprising a support, wherein said at least one fiber optic filament is coiled around said support, and wherein said support is housed within said at least one
5 encasement.

Sub
G6
17. A method of providing an ambient light collecting bow sight, comprising the steps of:

- a. coiling at least one fiber optic filament
10 around a support; and
- b. positioning one end of said at least one fiber optic filament within a bow sight.

18. The method of Claim 17, wherein said at least one
15 fiber optic filament is a plurality of fiber optic filaments.

adda7